


Z-3001 Handheld Laser Scanner

USB on Board

Standard Device



PIN-OUT CONFIGURATION			
RJ 1.	RTS_TTL	RJ 6.	RX_TTL
RJ 2.	KB Data	RJ 7.	KB Clock
RJ 3.	PC Clock	RJ 8.	+5V
RJ 4.	GND	RJ 9.	PC Data
RJ 5.	CTS_TTL	RJ10.	TX_TTL

Model No.	Part No.	Barcode Symbology	TYPE	REMARK
Z-3001	883-013000-00U		With Auto Sensor	Industrial white housing
Z-3001 (B)	883-013000-01U			Black housing
Z-3001	883-014000-00U		Without Auto Sensor	Industrial white housing
Z-3001 (B)	883-014000-01U			Black housing

Standard Cable Options

Please select a suitable cable from the following options according to your computer type/interface.

1. Keyboard Wedge Cable (for PS/2)

	<table border="1"> <thead> <tr> <th colspan="4">PIN-OUT CONFIGURATION</th> </tr> <tr> <th colspan="2">MINI DIN (M)</th> <th colspan="2">MINI DIN(F)</th> </tr> </thead> <tbody> <tr> <td>1.</td> <td>PC Data</td> <td>1.</td> <td>KB Data</td> </tr> <tr> <td>2.</td> <td>N.C.</td> <td>2.</td> <td>N.C.</td> </tr> <tr> <td>3.</td> <td>GND</td> <td>3.</td> <td>GND</td> </tr> <tr> <td>4.</td> <td>+5V</td> <td>4.</td> <td>+5V</td> </tr> <tr> <td>5.</td> <td>PC Clock</td> <td>5.</td> <td>KB Clock</td> </tr> <tr> <td>6.</td> <td>N.C.</td> <td>6.</td> <td>N.C.</td> </tr> </tbody> </table>				PIN-OUT CONFIGURATION				MINI DIN (M)		MINI DIN(F)		1.	PC Data	1.	KB Data	2.	N.C.	2.	N.C.	3.	GND	3.	GND	4.	+5V	4.	+5V	5.	PC Clock	5.	KB Clock	6.	N.C.	6.	N.C.
	PIN-OUT CONFIGURATION																																			
MINI DIN (M)		MINI DIN(F)																																		
1.	PC Data	1.	KB Data																																	
2.	N.C.	2.	N.C.																																	
3.	GND	3.	GND																																	
4.	+5V	4.	+5V																																	
5.	PC Clock	5.	KB Clock																																	
6.	N.C.	6.	N.C.																																	
Item Part No.	171-10K100-200																																			

2. RS-232C Communication Cable (DTE pin out)

	PIN-OUT CONFIGURATION	
	DB-9 (F)	FUNCTION
	2	TX
	3	RX
	7	CTS
	8	RTS
	5	GND
	9	+5V Input
Item Part No. 171-10R445-200		

3. RS-232C Communication Cable (DCE pin out)

	PIN-OUT CONFIGURATION	
	DB-9 (F)	FUNCTION
	2	RX
	3	TX
	7	RTS
	8	CTS
	5	GND
	9	+5V Input
Item Part No. 171-10R435-200		

4. USB Interface with Detachable Cable Type A



	PIN-OUT CONFIGURATION	
	USB TYPE A Connector	Function
	1.	VCC
	2.	D-
	3.	D+
	4.	VSS
Item Part No. 171-10U301-200		

Optional Stand Selections

Small Stand	Tall Stand	
P/N: 883-00HL00-001	P/N: 883-00ST00-000	P/N: 883-00ST00-001
Black	Industrial White Housing	Black Housing

Optional Accessories

Power Adapter



Part No.	Barcode Symbology	Plug	Output	Applicable Regions
11S-500050-001		UK Plug	5 VDC 1mA	United Kingdom, Scotland
11S-500051-001		US Plug	5VDC 1mA	North America, Japan, Taiwan
11S-500052-001		Australia Plug	5VDC 1mA	Australia
11S-500053-001		European Plug	5VDC 1mA	Europe, China, South East Asia, Middle East, South America